

## PowerMatic® Family of Low Energy Operators

| Characteristics of the Opening  | Sample Applications                |  | Series Recommended |
|---|------------------------------------|--|--------------------|
| Door to open via wall switch<br>Exterior door<br>Moderate to high usage               | Hospital                           | Patient Room   | 5700               |
|   | College or University              | Laboratory   |                    |
|   | Office Building                    | Executive Suite  |                    |
| Door to open via wall switch<br>Exterior door swinging 180°<br>Moderate to high usage | Hospital                           | Behavioral Health<br>Examination Rooms   | 6000               |
|   | Large Office Building              | Entrance Doors   |                    |
|   | College or University              |  |                    |
| Door to be held open 99% of the time  | K-12                               | Gymnasium Doors  | 6000               |
| Noise is a concern<br>Moderate usage  | Senior Housing/<br>Assisted Living | Cross Corridor   | 5900               |
|   | Convention Center                  | Exhibition Halls   |                    |
| Noise is a concern<br>Moderate usage  | Hospital                           | Maternity Ward<br>Patient Room   | 5900               |
|   | Office Building                    | Board/Meeting Rooms  |                    |
|   | College or University              | Auditorium/Lecture Halls   |                    |
|   | Places of Worship                  | Main Entrance Doors  |                    |
| Noise is a concern<br>Moderate usage  | College or University              | Dorm Rooms   | 5700               |
| Noise is a concern<br>High usage  | Government                         | Courtroom  | 5900               |
|   | K-12                               | Libraries  |                    |
| Non-fire rated door   | Retail                             | Stock Room Door  | 5600               |
|   | Office Building                    | Supply Closet  |                    |
|   |                                    | Private Office   |                    |
| Heavy usage<br>Mostly manual operation<br>ADA door                                    | Bank                               | Main Entrance Doors  | 6000               |
|   | Hospital                           |  |                    |
|   | Office Building                    | Board/Meeting Rooms  |                    |
|   | College or University              | Common Areas<br>Dormitory Entrances  |                    |
| Basic operator (non-fire rated door)  | Restaurant                         | Restroom   | 5600               |
| Vestibule blow-open doors required  | Sports Arena                       | Main Entrance or Smoke Evacuation Doors  | 6000               |
| Coordination of double doors required (left door must close first)                    | Hospital<br>Convention Center      | Utility Doors (catering, shipping/receiving, doors that are typically "behind the scenes") | 5900               |
| Doors need to open/close via operator   | Strip Mall                         | Main Entrance Doors  | 5900 or 6000       |

Norton Door Controls  
3000 Highway 74 East • Monroe, NC 28112  
Tel: 1-877-974-2255 • Fax: 1-800-338-0965

Norton® and PowerMatic® are registered trademarks of Yale Security Inc., an ASSA ABLOY Group company. These materials are protected under U.S. copyright laws. All contents current at time of publication. Copyright © 2012, Yale Security Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Yale Security Inc. is prohibited.

43190-12/12R